Drupal 8 Cache API

.and tacos





Märt Matsoo

Developer Tallinn, Estonia

Major: Back-End Minor: Front-End

Who?

Originally from Toronto, Canada

Lives in Tallinn, Estonia

Drupal since 2008

Works for Chromatic!





What is Chromatic?

Mostly Drupal-focused with Front End and DevOps expertise

Been around for over 10 years

Distributed (No head office. No office, period.)

https://chromatichq.com

Taco time...



Drupal 8 Cache API

.and tacos



Why cache at all?

- · Buy a Big Mac or buy the ingredients and make one at home?
- Minutes vs Hours
- · Cached page vs Non-cached page
- · Milliseconds vs Seconds
- · 281 milliseconds vs 2.97 seconds on my local





Drupal render arrays

- · Render arrays are the building blocks of a Drupal page
- · Introduced in Drupal 7 and allow for flexibility in extending / altering / overriding parts of the page
- print render(\$content);

```
<div class="content"<?php print $content_attributes; ?>>
    <?php
    print render($content);
    ?>
    </div>
```

- · It's important that our render array the thing that renders the HTML knows to cache itself
- From D.O.: "It is of the utmost importance that you inform the Render API of the cacheability of a render array." From Cacheability of Render Arrays*
 - * https://www.drupal.org/docs/8/api/render-api/cacheability-of-render-arrays



Originally a blog post





Got Slack? Get HeyTaco!





- HeyTaco! is an integration app for Slack
- · You hand out tacos to show appreciation and HeyTaco! keeps track of who gets them and how many they have.
- · 5 tacos to hand out each day.







Hey Taco! in Slack looks like this



davelook 19:56

@heytaco leaderboard



heytaco APP 19:56 ☆

Chromatic Leaderboard

- 1). chrisfree 380
- 2). ryanhagerty 347
- 3). alanna 343
- 4). larrywalangitan 298
- 5). adamzimmermann 292
- 6). davelook 280
- 7). guschilds 262
- 8). markdorison 234
- 9). mart 227
- 10). ctorgalson 215



HeyTaco! API

```
- HeyTaco!
```

API

```
// Using Guzzle.
$response = \Drupal::httpClient()->get(HEYTACO_URL);
// Get JSON from HeyTaco.
$json_string = (string) $response->getBody();
$leaderboard = array_shift(json_decode($json_string, TRUE));
```

There is one main object in our API: Leaderboard. We currently only offer a JSON response format. If you have any questions please contact us.

Leaderboard

Retrieve your team leaderboard (Sign in to HeyTaco! to display your team id below):

https://www.heytaco.chat/api/v1/json/leaderboard/{%teamId%}?days=1


Example JSON Response

```
{
    "leaderboard": [{
        "received_by_id": "U123456789",
        "username": "test",
        "team_name": "Test",
        "avatar": "https://secure.gravatar.com/avatar/9828a53f505ab5ea9c7daedee91.png",
        "timestamp": "2016-11-12T10:30:32.000Z",
        "count": "1"
    }]
}
```



What's the plan?

- · drush core-quick-drupal ("qd", "cutie")
- · Drupal 8 custom module creates a Block
- Custom code grabs leaderboard from HeyTaco!
 ChromaticHQ/heytaco)



- · Use D8 Cache settings to cache it separately for each user
- · Add bonus tacos to the bosses' totals to make them think they're great
- · A bit of Twig to theme it (heytaco-block.html.twig)



Partner vs Non-partner Leaderboards

HeyTaco! Leaderboard

Hi chrisfree!

- 1. chrisfree 486
- 2. davelook **386**
- 3. alanna **363**
- 4. ryanhagerty **35**7
- 5. markdorison **341**
- 6. larrywalangitan **306**
- 7. adam **297**
- 8. guschilds **270**
- 9. märt **234**
- 10. ctorgalson 229

HeyTaco! Leaderboard

Hi alanna!

- 1. chrisfree 486 *
- 2. davelook 386 *
- 3. alanna **363**
- 4. ryanhagerty **357**
- 5. markdorison **341** *
- 6. larrywalangitan **306**
- 7. adam **297**
- 8. guschilds **270**
- 9. märt **234**
- 10. ctorgalson 229




^{*} Partners' results padded by 100 tacos

```
* Provides a Hey Taco Results block
* @Block(
    id = "heytaco_block",
    admin label = @Translation("HeyTaco! Leaderboard"),
* )
*/
class HeyTacoBlock extends BlockBase implements ContainerFactoryPluginInterface {
 /**
  * construct() and create() functions here
 **/
 /**
   * {@inheritdoc}
  */
 public function build() {
   $user_id = $this->account->id();
   return array(
      '#theme' => 'heytaco_block',
      '#results' => $this->returnLeaderboard($user_id),
      '#partner_asterisk_blurb' => $this->isNotPartner($user_id),
      '#cache' => [
        'keys' => ['heytaco_block'],
        'contexts' => ['user'],
        'tags' => ['user_list'],
        'max-age' => 3600,
```



HeyTaco Leaderboard block





#cache property's metadata

- · keys
- contexts
- · tags
- · max-age



```
/**
* {@inheritdoc}
public function build() {
 // Dependency injection used create() and __construct() pattern.
  $user_id = $this->account->id();
  return array(
    '#theme' => 'heytaco_block',
    '#results' => $this->returnLeaderboard($user_id),
    '#partner_asterisk_blurb' => $this->isNotPartnerBlurb($user_id),
    '#display_name' => $this->account->getUsername(),
    '#cache' => [
      'keys' => ['heytaco_block'],
      'contexts' => ['user'],
      'tags' => ['user_list'],
      'max-age' => 3600,
```



```
/**
* {@inheritdoc}
public function build() {
  // Dependency injection used create() and __construct() pattern.
  $user_id = $this->account->id();
  return array(
    '#theme' => 'heytaco_block',
    '#results' => $this->returnLeaderboard($user_id),
    '#partner_asterisk_blurb' => $this->isNotPartnerBlurb($user_id),
    '#display_name' => $this->account->getUsername(),
    '#cache' => [
      'keys' => ['heytaco_block'],
      'contexts' => ['user'],
      'tags' => ['user_list'],
      'max-age' => 3600,
  );
```



```
* {@inheritdoc}
public function build() {
 // Dependency injection used create() and __construct() pattern.
 $user_id = $this->account->id();
  return array(
    '#theme' => 'heytaco_block',
    '#results' => $this->returnLeaderboard($user_id),
    '#partner_asterisk_blurb' => $this->isNotPartnerBlurb($user_id),
    '#display_name' => $this->account->getUsername(),
    '#cache' =>
      'keys' => ['heytaco_block'],
      'contexts' => ['user'],
      'tags' => ['user_list'],
      'max-age' => 3600,
```



keys

```
'#cache' => [
   'keys' => ['heytaco_block'],
   'contexts' => ['user'],
   'tags' => ['user_list'],
   'max-age' => 3600,
],
```

- · From Drupal.org: ...what identifies the thing I'm rendering?
- · This is the "what", as in "What entity is being rendered?"
- · Can be more than a single string

```
'#cache' => [
  'keys' => ['view', $view_id, 'display', $display_id],
],
```

· Cache keys must only be set if the render array should be cached



contexts

```
'#cache' => [
   'keys' => ['heytaco_block'],
   'contexts' => ['user'],
   'tags' => ['user_list'],
   'max-age' => 3600,
],
```

- · From Drupal.org: Does the representation of the thing I'm rendering vary per ... something?
- · This is the "which", as in, "Which version of the block should be shown?"
- Contexts aren't just user-based; they can also be based on cookies
 ip
 theme
 timezone
 url
 and more...modules can also define their own (https://www.drupal.org/docs/8/api/cache-api/cache-contexts)
- · There is a list of cache contexts in core.services.yml



tags

```
'#cache' => [
  'keys' => ['heytaco_block'],
  'contexts' => ['user'],
  'tags' => ['user_list'],
  'max-age' => 3600,
],
```

- From Drupal.org: What data does it depend upon, so that when that data changes, so should the representation?
- · String, cannot contain spaces, generally in the form <entity type>:<entity ID>
- · Can be in sets: ['user:3', 'user:4', 'user:5']

```
HeyTaco! Leaderboard

Hi märt!

1. chrisfree 486 *
2. davelook 386 *
3. alanna 363
4. ryanhagerty 357
5. markdorison 341 *
6. larrywalangitan 306
7. adam 297
8. guschilds 270
9. märt 234
10. ctorgalson 229

*Partners' results padded by 100 tacos
```

```
HeyTaco! Leaderboard

Hi Märt Matsoo!

1. chrisfree 486 *
2. davelook 386 *
3. alanna 363
4. ryanhagerty 357
5. markdorison 341 *
6. larrywalangitan 306
7. adam 297
8. guschilds 270
9. Märt Matsoo 234
10. ctorgalson 229

* Partners' results padded by 100 tacos
```



max-age

```
'#cache' => [
  'keys' => ['heytaco_block'],
  'contexts' => ['user'],
  'tags' => ['user_list'],
  'max-age' => 3600,
],
```

- · Max amount of time to cache this rendering
- Measured in seconds (3600 = 1 hour)
- · Defaults to forever (Cache::PERMANENT)



Helpful Info from D.O.

From D.O.*: Cache contexts, tags and max-age must always be set, because they affect the cacheability of the entire response. Therefore they "bubble": parents [ie. the page that contains our Hey Taco block] automatically receive them.

and...

Cache keys must only be set if the render array should be cached.

* https://www.drupal.org/docs/8/api/render-api/cacheability-of-render-arrays



Theming

```
/**
* {@inheritdoc}
public function build() {
 // Dependency injection used create() and __construct() pattern.
 $user_id = $this->account->id();
  return array(
    '#theme' => 'heytaco_block',
    '#results' => $this->returnLeaderboard($user_id),
    '#partner_asterisk_blurb' => $this->isNotPartnerBlurb($user_id),
    '#display_name' => $this->account->getUsername(),
    '#cache' => [
     'keys' => ['heytaco_block'],
     'contexts' => ['user'],
      'tags' => ['user_list'],
      'max-age' => 3600,
```



Theming

```
/**
* {@inheritdoc}
public function build() {
 // Dependency injection used create() and __construct() pattern.
 $user_id = $this->account->id();
  return arrav(
   '#theme' => 'heytaco_block',
    '#results' => $this->returnLeaderboard($user_id),
    '#partner_asterisk_blurb' => $this->isNotPartnerBlurb($user_id),
    '#display_name' => $this->account->getUsername(),
    '#cache' => [
     'keys' => ['heytaco_block'],
      'contexts' => ['user'],
      'tags' => ['user_list'],
      'max-age' => 3600,
```



heytaco.module

```
heytaco.info.yml
heytaco.module
heytaco.routing.yml
src
templates
heytaco-block.html.twig
```

```
* Implements hook_theme().
function heytaco_theme($existing, $type, $theme, $path) {
  return array(
    'heytaco_block' => array(
      'variables' => array(
        'results' => NULL,
        'partner_asterisk_blurb' => NULL,
        'display_name' => NULL
      ),
```



heytaco-block.html.twig

HeyTaco! Leaderboard

Hi Märt Matsoo!

- 1. chrisfree **486** *
- 2. davelook 386 *
- 3. alanna **363**
- 4. ryanhagerty 357
- 5. markdorison **341***
- 6. larrywalangitan **306**
- 7. adam **297**
- 8. guschilds **270**
- 9. Märt Matsoo 234
- 10. ctorgalson **229**



^{*} Partners' results padded by 100 tacos

In Cache-tastic Conclusion

- · Cache metadata: keys, contexts, tags, max-age
- '#partner_asterisk_blurb' => \$this'#cache' => [
 'keys' => ['heytaco_block'],
 'contexts' => ['user'],
 'tags' => ['user_list'],
 'max-age' => 3600,
],
- · Render arrays and the #cache property go hand in hand
- · Try different use cases to better grasp what each metadata piece does
- · Sample code: https://github.com/ChromaticHQ/heytaco



Thanks!

Märt Matsoo

twitter @mmatsoo

Chromatic

https://chromatichq.com

